

Rivelatori filari da incasso

Wired flush mounted detectors

531

AF441062 AF449062 AF445062

AF441062
Rivelatore via filo PIR da incasso. Assorbimento 7mA. Portata 10m.
S44 serie Domus
Wired PIR flush mounted detector. Consumption range 7mA. Range 10 m. S44 Domus series.

1 1

AF442062
Come sopra. S44 serie Life.
See above. S44 Life series.

1 1

AF443062
Come sopra. S44 serie Allumia.
See above. S44 Allumia series.

1 1

AF445062
Come sopra. S44 serie Tekla.
See above. S44 Tekla series.

1 1

AF442062 AF443062

AF449062
Come sopra. S44 serie Class.
See above. S44 Class series.




1 1

Nota: prevedere un contatto ausiliario per la protezione antirimozione del dispositivo.
Note: please provide an auxiliary contact to ensure the tamper protection of the device.



Rivelatori filari volumetrici da parete







Wired volumetric wall mounted detectors

Descrizione Description		Info	€	<input type="checkbox"/>	<input type="checkbox"/>
	AF962 Rivelatore via filo PIR Contaimpuls. Portata 15m. Assorbimento 7mA. <i>Wired PIR detector. Impulse counter. 15m range. 7mA current consumption.</i>			1	1
	AF961 Snodo per rivelatori a parete. Per AF962, AF968R-DB e AF974R-DB. <i>Adjustable joint for detectors. For AF962, AF968R-DB and AF974R-DB.</i>			1	10
	AF963N Rivelatore doppia tecnologia con antiaccecamento. Assorbimento 30mA. Fornito con snodo. <i>Dual technology detector with anti-blinding. 30mA current consumption. Joint included.</i>			1	1

AF963N


Rivelatori radio volumetrici da parete

Wireless volumetric wall mounted detectors

Descrizione Description		Info	€	<input type="checkbox"/>	<input type="checkbox"/>
	AF968R-DB Rivelatore AF914R-MDB PIR via radio. Trasmissione in doppia frequenza, Dual Band. Dimensioni: 70x140x40mm <i>PIR radio detector. Dual band transmission. Dimensions: 70x140x40mm</i>			1	1
	AF961 Snodo per rivelatori a parete. Per AF962, AF968R-DB e AF974R-DB. <i>Adjustable joint for detectors. For AF962, AF968R-DB and AF974R-DB.</i>			1	10
	AF963R-DB Rivelatore PIR via radio. Trasmissione in doppia frequenza, Dual Band. Batteria: 1xCR123 inclusa. Colore RAL 9016. Dimensioni: 68 x 51 x 112 mm. <i>Radio PIR detector. Dual frequency transmission, Dual Band. Battery: 1xCR123 included. Colour RAL 9016. Dimensions: 68 x 51 x 112 mm</i>			1	1
	AF961N Snodo angolare per rivelatore AF963R-DB. Dimensioni: 68 x 51 x 112 mm. <i>Angular joint for detector AF963R-DB. Dimensions: 68 x 51 x 112 mm</i>			1	10

AF961N
AF963R-DB

Le dimensioni, salvo diversamente specificato, sono in mm
Dimensions, except where otherwise specified, are in mm

Prodotto per Export
For Export only

Imballo Minimo pcs
Min. Packaging pcs

Imballo Standard pcs
Std. Packaging pcs