



Rivelatori radio da esterno e/o esterno riparato

Wireless outdoor and/or sheltered outdoor detectors

537



AF975R-DB



AF974R-DBS



AF974R-DB



AF965R-DB

per /for
AF949PLUS - AF999PLUS

AF974R-DB

Rivelatore doppia tecnologia radio per esterno riparato. Trasmissione dual band. Compatibile con tutte le centrali radio AVE (AF926PLUS, AF949PLUS e AF999PLUS). Da completare con snodo AF961. Alimentazione: 3 batterie AA 1,5V. Dimensioni 155x87x48mm.
Dual technology radio detector for sheltered outdoor use. Dual band transmission. It can be used with all the radio central units made by AVE (AAF926PLUS, AF949PLUS and AF999PLUS). To be completed with AF961 joint. Power supply: 3 1,5V AA batteries. Dimensions 155x87x48mm.

1 1

AF974R-DBS

Snodo e cover per AF974R-DB. Permette la corretta protezione del rivelatore AF974R-DB. Joint and cover for AF974R-DB. It allows the correct protection of the AF974R-DB detector.

1 1

AF975R-DB

Rivelatore perimetrale radio dual band a doppio sensore PIR e antiaccecamento. L'allarme avviene attraversando entrambe le barriere create dai PIR, oppure prima quella esterna, poi quella interna (non il contrario): le due possibilità sono selezionabili in funzione dell'utilizzo. Portata 8m. Classe ambientale III (esterno riparato). Batteria CR123. Dimensioni: 80x80x23mm.
Da utilizzare solo con centrali AF949PLUS - AF999PLUS - AF926PLUS
Dual band radio curtain effect detector with double PIR and anti-blinding functional. The alarm is sent only if you go through both the two curtains created by the 2 PIR or if you go through the external curtain and then thorough the internal one (it doesn't work in the reverse way). The installer can select the two different functions. Range 8m. CLASS III (Sheltered outdoor or indoor extreme conditions). Battery CR123. Dimensions: 80x80x23mm.
To be used only with control unit AF949PLUS - AF999PLUS - AF926PLUS

1 1

per /for
AF927PLUS - AF927PLUSTC

AF965R-DB

Rivelatore perimetrale radio dual band a doppio sensore PIR e antiaccecamento. L'allarme avviene attraversando entrambe le barriere create dai PIR, oppure prima quella esterna, poi quella interna (non il contrario): le due possibilità sono selezionabili in funzione dell'utilizzo. Portata 8 m. Classe ambientale III (esterno riparato). Batteria: 1xCR123 inclusa. Colore RAL 9016. Dimensioni: 79x23x79 mm.
Da utilizzare solo con centrali AF927PLUS - AF927PLUSTC
Dual band radio perimeter detector with dual sensor PIR and anti-blinding. The alarm is triggered by crossing both barriers created by the PIR sensors, or first the outdoor one, then the indoor one (not the opposite); the two options can be selected according to use. Range 8 m. Environmental class III (outdoor sheltered). Battery: 1xCR123 included. Colour RAL 9016. Dimensions: 79x23x79 mm.
To be used only with control unit AF927PLUS - AF927PLUSTC



1 1

Combinatori telefonici Telephone diallers



AF986GSM



AFGSM03



AFGSM04

Descrizione Description

Info

€

□

□

AF986GSM

Combinatore telefonico via filo bidirezionale GSM. 4 canali vocali, 4 canali SMS e 6 SMS tecnici. 2 uscite open collector comandabili anche da SMS. Tastiera alfanumerica e display LCD a bordo. Da completare con 2 batterie AF916. Alimentazione 10-14Vcc. Dimensioni 161x110x30 mm.
Hardwired two-way GSM telephone dialler. 4 channels with vocal messages, 4 channels with SMS and 6 technical SMS. 2 open collector outputs that you can manage also via SMS. Alphanumeric keyboard and LCD on board. To be completed with 2 AF916 batteries. Power Supply: 10-14Vdc. Dimensions 161x110x30 mm.

1 1

Per/For
AF999PLUS
AF949PLUS

AFGSM03

Modulo GSM per combinatore telefonico. Collegato alla scheda madre delle centrali AF999EXP e AF949, permette la trasmissione degli allarmi delle centrali AF999EXP e AF949 sulla linea GSM. Permette il controllo completo della centrale anche tramite SMS.
GSM module for telephone dialler. Connected to the main board of the AF999EXP and AF949 central units it allows to transmit via the GSM network the alarms coming from the AF999EXP and AF949 central units. It allows the complete control of the central unit also via SMS.

1 1

per /for
AF927PLUS
AF927PLUSTC

AFGSM04

Modulo GSM 2G per centrali AF927PLUS e AF927PLUSTC. Innesto a pettine in centrale. Consente invio e ricezione di SMS e chiamate vocali per la gestione bidirezionale della centrale.
GSM 2G module for AF927PLUS and AF927PLUSTC control units. Comb coupling to the control unit. Allows SMS and voice calls to be sent and received for two-way management of the control unit.



1 1



Nota: disponibile prolunga per l'antenna dei moduli GSM (AFGSM03). Per la disponibilità contattare la rete commerciale
Note: extension for the antenna of the GSM module available (AFGSM03). For availability please contact sales dept.