

	Descrizione Description	Info	€	<input type="checkbox"/>	<input type="checkbox"/>	359
 251CG	<b>251CG</b> Scatola tonda 1-2 mod. S44 e S45 - dimensioni (Ø P): 68x68x46mm 1-2 modules S44 and S45 round box - dimensions (Ø D): 68x68x46 mm					40 40
 253CGPR	<b>253CGPR</b> Scatola rettangolare 3 mod. S44 e S45 con profondità ridotta interasse viti 83,5 mm - dimensioni (L H P): 113x70x46mm 3 modules S44 and S45 rectangular box with reduced depth screws fixing centres 83,5 mm - dimensions (L H D): 113x70x46 mm					180 180
 253CG	<b>253CG</b> Scatola rettangolare 3 mod. S44 e S45 - interasse viti 83,5 mm - dimensioni (L H P): 109x70x51 mm 3 modules S44 and S45 rectangular box - screws fixing centres 83,5 mm - dimensions (L H D): 109x70x51 mm					225 225
 253X4CGPR	<b>253X4CG*</b> Scatola rettangolare 3 e 4 mod. per serie civili* S44 e S45 - interasse viti 83,5 mm e 108,5 mm - dimensioni (L H P): 122x79x51 mm 3 and 4 modules rectangular box for wiring accessories* S44 and S45 - screws fixing centres 83,5 mm and 108,5 mm - dimensions (L H D): 122x79x51 mm					150 150
 253CG	<b>254CGPR</b> Scatola rettangolare 4 mod. S44 e S45 con profondità ridotta interasse viti 108,5 mm - dimensioni (L H P): 138x69x46 mm 4 modules S44 and S45 rectangular box with reduced depth screws fixing centres 108,5 mm - dimensions (L H D): 138x69x46 mm					100 100
 254CG	<b>254CG</b> Scatola rettangolare 4 mod. S44 e S45 - interasse viti 108,5 mm dimensioni (L H P): 132x70x51 mm 4 modules S44 and S45 rectangular box - screws fixing centres 108,5 mm dimensions (L H D): 132x70x51 mm					96 96
 253X4CG	<b>256CG</b> Scatola rettangolare 6 mod. S45 e 7 mod. S44 - interasse viti orizzontale 100 mm e verticale 57,5 mm - dimensioni (L H P): 188x68x51 mm 6 modules S45 and 7 modules S44 rectangular box - screws fixing centres horizontal 100 mm and vertical 57,5 mm - dimensions (L H D): 188x68x51 mm					22 22
 254CGPR	<b>GWEPT</b> (resistenza al fuoco): 850°C - <b>Materiale:</b> Tecnopolimero autoestinguente <b>GWEPT</b> (flame resistance): 850°C - <b>Material:</b> self-extinguishing technopolymer					
 254CG	* Serie civili compatibili: <b>AVE S44</b> AVE Touch, Life, Allumia, Domus, Tekla, Class; <b>S45</b> Noir AX, Banquise, Blanc, RAL; <b>Bticino</b> Air, Axolute, Livinglight, Matix; <b>Vimar</b> Eikon, Arkè, Plana, Idea; <b>Gewiss</b> Chorus e con le altre serie civili, purché la placca da 3 moduli abbia una larghezza minima di 118 mm. * Compatible wiring accessories series: <b>AVE S44</b> AVE Touch, Life, Allumia, Domus, Tekla, Class; <b>S45</b> Noir AX, Banquise, Blanc, RAL; <b>Bticino</b> Air, Axolute, Livinglight, Matix; <b>Vimar</b> Eikon, Arkè, Plana, Idea; <b>Gewiss</b> Chorus and all the other wiring accessories series if the 3 modules front plate have a minimum width of 118mm.					
 256CG						

SCATOLE CONTENITORI  
CENTRALINI  
BOXES ENCLOSURES  
CONSUMER UNITS

 TÜVRheinland®  
Certificazioni Isolamento termo-acustico pagina dedicata  
Certification for thermo-acoustic isolation dedicated page

Scatole speciali per installazioni filo muro Special boxes for wall-lined installation

	Descrizione Description	Info	€	<input type="checkbox"/>	<input type="checkbox"/>	
 SFM3CG/HP	<b>SFM3CG/HP</b> Scatola ad "alta precisione" 3 moduli - interasse viti 83,5 mm - fornita con dima di foratura, livella a bolla e cornice completa di supporto 3 mod. S44 - dimensioni 167x148x60mm 3 modules "high precision" box - screw fixing centre 83,5 mm - supplied with template, spirit level and System 44 3 modules frame - dimensions 167x148x60mm					1 1

Le dimensioni, salvo diversamente specificato, sono in mm  
Dimensions, except where otherwise specified, are in mm

 Prodotto  
per Export  
For Export  
only

Imballo Minimo pcs  
Min. Packaging pcs

Imballo Standard pcs  
Std. Packaging pcs