








Prodotti per ricambistica
Spare parts products

		Descrizione <i>Description</i>	Info	€	<input type="checkbox"/>	<input type="checkbox"/>
<div style="border: 1px solid green; border-radius: 15px; padding: 10px; margin-bottom: 10px;">  <p>Per la disponibilità contattare la rete commerciale <i>For availability please contact sales dept.</i></p> </div>  <p>SF910</p>  <p>SF91T</p>  <p>AC910</p>  <p>AC9C1-IS AC9M1-IS</p>  <p>PE09IND</p>  <p>AC910</p>	<p>AC9M1-IS Modulo indirizzabile ad un ingresso per centrali AC921, AC922, AC924. <i>One input addressed module for AC921, AC922, AC924 detector units.</i></p>	1	1			
	<p>SF910T Rivelatore ottico/termico indirizzato per centrali AC921, AC922, AC924. <i>Addressed smoke/thermal detector for AC921, AC922, AC924 central units.</i></p>	1	1			
	<p>SF910 Rivelatore ottico di fumo indirizzato, per centrali AC921, AC922, AC924. <i>Addressed optical smoke detector for AC921, AC922, AC924 central units.</i></p>	1	1			
	<p>SF91T Rivelatore termovelocimetrico indirizzato, per centrali AC921, AC922, AC924. <i>Addressed rate of rise heat detector for AC921, AC922, AC924 central units.</i></p>	1	1			
	<p>SF9B Base per rivelatori SF910, SF91T, SF910T. <i>Base for SF910, SF910T, SF91T detectors.</i></p>	1	1			
	<p>AC9C1-IS Modulo indirizzabile ad un'uscita con isolatore per centrali AC921, AC922, AC924. <i>One output addressed module with isolation for AC921, AC922, AC924 central units.</i></p>	1	1			
	<p>PE09IND Pulsante manuale indirizzato a rottura vetro per centrali analogiche completo di isolatore di corto circuito. Membrana riarmabile fornibile a richiesta. <i>Addressed break glass call point for analogic central unit, with short-circuit insulator included. Available with resettable membrane (upon request).</i></p>	1	1			
	<p>AC910 Sirena indirizzabile con isolatore. Alimentata da loop. Assorbimento a riposo 120 µA in allarme 3,7mA. Pressione acustica 102 db a 1 m. <i>Addressed sounder with isolator. Powered by loop. Stand-by consumption 120µA, 3,7mA in alarm condition. Acoustic pressure: 102dB at 1 m.</i></p>	1	1			
	<p>AC911 Base per sirena indirizzabile AC910. <i>Base for addressed sounder AC910.</i></p>	1	1			