







Rivelatori radio perimetrali *Wireless perimeter detectors*

		Descrizione <i>Description</i>	Info	€	<input type="checkbox"/>	<input type="checkbox"/>
		per /for AF949PLUS - AF999PLUS AF914R-DB Rivelatore perimetrale via radio colore bianco, per centrali AF949PLUS, AF999PLUS e AF926PLUS. Trasmissione in doppia frequenza (Dual band). Segnale di allarme differenziato per contatto magnetico e ingresso ausiliario della morsetteria. Dimensioni (136x31x28mm). <i>Wireless perimeter detector white colour, for AF949PLUS, AF999PLUS and AF926PLUS central units. Dual band transmission. Different alarm signals for magnetic contact and auxiliary onboard input. Dimensioni (136x31x28mm).</i>	1	1		
			AF914R-MDB Come sopra - colore marrone. <i>See above - brown colour.</i>	1	1	
		per /for AF927PLUS - AF927PLUSTC AF915R-DB Rivelatore perimetrale via radio per centrali AF927PLUS e AF927PLUSTC - bianco. Trasmissione in doppia frequenza (Dual band). Segnale di allarme differenziato per contatto magnetico e 2 ingressi ausiliari della morsetteria. Doppio reed di cui uno per funzione tamper magnetico. Batteria: 1xCR123 inclusa. Colore RAL 9016. Dimensioni del contatto: 23 x 25 x 134 mm. <i>Radio perimeter detector for AF927PLUS and AF927PLUSTC central units - white. Dual frequency transmission (Dual Band). Differentiated alarm signal for magnetic contact and 2 auxiliary inputs of the terminal board. Double reed, one of which for magnetic tamper function. Battery: 1xCR123 included. Colour RAL 9016. Dimensions of the contact: 23 x 25 x 134 mm.</i>	1	1		
			AF915R-MDB Come sopra - colore marrone. <i>See above - brown colour.</i>	1	1	

Rivelatori filari da esterno *Wired outdoor detectors*



		Descrizione <i>Description</i>	Info	€	<input type="checkbox"/>	<input type="checkbox"/>
		AF969F Rivelatore doppia tecnologia a tenda per la protezione di varchi. Portata massima: 12m. Assorbimento 32mA. Conforme alla norma EN 50131-2-4 Grado 2. Classe ambientale IV (esterno). Dimensioni (110x44x46mm). Fornito con tettuccio, staffa per montaggio angolare (90°) e lente PET immunity. <i>Dual technology curtain detector for the protection of openings. Maximum range: 12m. Current consumption 32mA. Standard compliance: EN50131-2-4 Grade 2, CLASS IV (Outdoor). Dimensions (110x44x46mm). Protection cover, angle bracket and PET immunity lens included.</i>	1	1		
			AF969S Snodo per AF969F. <i>Joint for AF969F.</i>	1	1	

DOMOTICA
Home Automation

GESTIONE ALBERGHIERA
Hotel Management Systems

DIVISIONE SICUREZZA
SAFETY-SECURITY