













## Rivelatori radio perimetrali Wireless perimeter detectors

Descrizione Description		Info	€	<input type="checkbox"/>	<input type="checkbox"/>	
		<b>per /for AF949PLUS - AF999PLUS</b>	<b>AF914R-DB</b> Rivelatore perimetrale via radio, colore bianco, per centrali AF949PLUS, AF999PLUS e AF926PLUS. Trasmissione in doppia frequenza (Dual band). Segnale di allarme differenziato per contatto magnetico e ingresso ausiliario della morsettiere. Dimensioni: 136x31x28mm. <i>Wireless perimeter detector, white colour, for AF949PLUS, AF999PLUS and AF926PLUS central units. Dual band transmission. Different alarm signals for magnetic contact and auxiliary onboard input. Dimensions: 136x31x28mm.</i>	142,53	1	1
			<b>AF914R-MDB</b> Come sopra - colore marrone. <i>See above - brown colour.</i>	139,90	1	1
		<b>per /for AF927PLUS - AF927PLUSTC</b>	<b>AF915R-DB</b> Rivelatore perimetrale via radio, colore bianco RAL 9016, per centrali AF927PLUS e AF927PLUSTC. Trasmissione in doppia frequenza (Dual band). Segnale di allarme differenziato per contatto magnetico e n.2 ingressi ausiliari della morsettiere. Doppio reed di cui uno per funzione tamper magnetico. Batteria: 1xCR123 inclusa. Dimensioni: 23x25x134mm. <i>Radio perimeter detector, white RAL 9016 colour, for AF927PLUS and AF927PLUSTC central units. Dual frequency transmission (Dual Band). Differentiated alarm signal for magnetic contact and n.2 auxiliary inputs of the terminal board. Double reed, one of which for magnetic tamper function. Battery: 1xCR123 included. Dimensions: 23x25x134mm.</i>	82,65	1	1
			<b>AF915R-MDB</b> Come sopra - colore marrone. <i>See above - brown colour.</i>	82,65	1	1

## Rivelatori filari da esterno Wired outdoor detectors



Descrizione Description		Info	€	<input type="checkbox"/>	<input type="checkbox"/>
		<b>AF969F</b> Rivelatore doppia tecnologia a tenda per la protezione di varchi. Portata massima: 12m. Assorbimento 32mA. Conforme alla norma EN 50131-2-4 Grado 2. Classe ambientale IV (esterno). Dimensioni: 110x44x46 mm. Fornito con tettuccio, staffa per montaggio angolare (90°) e lente PET immunity. <i>Dual technology curtain detector for the protection of openings. Maximum range: 12m. Current consumption 32mA. Standard compliance: EN50131-2-4 Grade 2, CLASS IV (Outdoor). Dimensions: 110x44x46 mm. Protection cover, angle bracket and PET immunity lens included.</i>	226,30	1	1
		<b>AF969S</b> Snodo per AF969F. <i>Joint for AF969F.</i>	21,36	1	1
		<b>AF974F</b> Rivelatore volumetrico di movimento a triplo sensore: doppio PIR (passive infra-red detector che rileva elementi di temperatura differente rispetto allo sfondo generando un allarme) e microonda (che analizza le radiazioni riflesse di un corpo in movimento). Portata massima: 12m. Assorbimento 45mA. Conforme alla norma EN 50131-2-4 CLASSE III GRADO 2. Dimensioni: 185X85X80 mm. Fornito con tettuccio. <i>Triple-sensor volumetric motion detector: double PIR (passive infra-red detector that detects elements of different temperature than the background, generating an alarm) and microwave (which analyzes the reflected radiation of a moving body). Maximum range: 12m. Current consumption 45mA. Standard compliance: EN 50131-2-4 CLASSE III GRADO 2. Dimensions: 185X85X80 mm. Protection cover included.</i>	 244,11	1	1
		<b>AF974S</b> Snodo per AF974F. <i>Joint for AF974F.</i>	 18,99	1	1

Le dimensioni, salvo diversamente specificato, sono in mm  
Dimensions, except where otherwise specified, are in mm

Prodotto per Export  
For Export only

Imballo Minimo pcs  
Min. Packaging pcs

Imballo Standard pcs  
Std. Packaging pcs

DOMOTICA  
Home Automation

GESTIONE ALBERGHERIA  
HOTEL MANAGEMENT  
SYSTEMS

DIVISIONE SICUREZZA  
SAFETY-SECURITY