



SF910



SF91T



AC9C1-IS  
AC9M1-IS



PE09IND



AC910

Descrizione Description	Info	€	□	□
<b>AC9M1-IS</b> Modulo indirizzabile ad un ingresso per centrali AC921, AC922, AC924. <i>One input addressed module for AC921, AC922, AC924 detector units.</i>		229,59	1	1
<b>AC9971</b> Sirena indirizzata per centrale AC902LP. <i>Sounder for AC902LP central unit.</i>		212,83	1	1
<b>SF910T</b> Rivelatore ottico/termico indirizzato per centrali AC921, AC922, AC924. <i>Addressed smoke/thermal detector for AC921, AC922, AC924 central units.</i>		172,46	1	1
<b>SF910</b> Rivelatore ottico di fumo indirizzato, per centrali AC921, AC922, AC924. <i>Addressed optical smoke detector for AC921, AC922, AC924 central units.</i>		268,00	1	1
<b>SF91T</b> Rivelatore termovelocimetrico indirizzato, per centrali AC921, AC922, AC924. <i>Addressed rate of rise heat detector for AC921, AC922, AC924 central units.</i>		165,44	1	1
<b>SF9B</b> Base per rivelatori SF910, SF91T, SF910T. <i>Base for SF910, SF91T, SF910T detectors.</i>		26,41	1	1
<b>AC9C1-IS</b> Modulo indirizzabile ad un'uscita con isolatore per centrali AC921, AC922, AC924. <i>One output addressed module with isolation for AC921, AC922, AC924 central units.</i>		250,98	1	1
<b>PE09IND</b> Pulsante manuale indirizzato a rottura vetro per centrali analogiche completo di isolatore di corto circuito. Membrana riarmabile fornibile a richiesta. <i>Addressed break glass call point for analogic central unit, with short-circuit insulator included. Available with resettable membrane (upon request).</i>		263,19	1	1
<b>AC910</b> Sirena indirizzabile con isolatore. Alimentata da loop. Assorbimento a riposo 120 µA in allarme 3,7mA. Pressione acustica 102 db a 1 m. <i>Addressed sounder with isolator. Powered by loop. Stand-by consumption 120µA, 3,7mA in alarm condition. Acoustic pressure: 102dB at 1 m.</i>		224,36	1	1
<b>AC911</b> Base per sirena indirizzabile AC910. <i>Base for addressed sounder AC910.</i>		29,13	1	1